

1 MONTHLY USAGE CHARGE:

2	5/8" x 3/4" Meter	\$12.00
	3/4" Meter	16.00
3	1" Meter	20.00
	1 1/2" Meter	35.00
4	2" Meter	60.00
	3" Meter	100.00
5	4" Meter	200.00
	6" Meter	350.00

6 COMMODITY CHARGE

7	Charge per 1,000 Gallons	\$5.00
	Standpipe - Charge per 1,000 gallons	\$5.00

8 SERVICE LINE AND METER INSTALLATION CHARGES:

9 (Refundable pursuant to A.A.C. R14-2-405)

10	5/8" x 3/4" Meter	\$ 370.00
	3/4" Meter	415.00
11	1" Meter	480.00
	1 1/2" Meter	700.00
12	2" Meter - Compound	1,760.00
	3" Meter - Compound	2,300.00
13	4" Meter - Compound	3,325.00
	6" Meter - Compound	6,430.00

14 SERVICE CHARGES:

15	Establishment	\$25.00
16	Establishment (After Hours)	\$37.50
	Reconnection (Delinquent)	\$35.00
17	Meter Test (If Correct)	\$40.00
	Deposit	*
18	Deposit Interest	*
	Reestablishment (Within 12 Months)	**
19	NSF Check	\$15.00
	Deferred Payment (Per Month)	1.5%
20	Meter Reread (If Correct)	\$ 25.00
	Late Payment Penalty (Per Month)	1.5%

21 Monthly Service Charge for Fire Sprinkler:

22	4" or Smaller	***
	6"	***
23	8"	***
	10"	***
24	Larger than 10"	***

25 * Per Commission Rule A.A.C. R14-2-403(B).

26 ** Months off system times the monthly minimum per Commission rule A.A.C. R14-2-403(D).

27 *** 1% of Monthly Minimum for a Comparable Sized Meter Connection, but no less than \$5.00 per month. The Service Charge for Fire Sprinklers is only applicable for service lines separate and distinct from the primary water service line.

28

CROSS-CONNECTION OR BACKFLOW TARIFF

PURPOSE:

The purpose of this tariff is to protect Rincon Water Company (Company) water from the possibility of contamination caused by the backflow of contaminants that may be present on the customers's premises by requiring the installation and periodic testing of backflow-prevention assemblies pursuant to the provisions of the Arizona Administrative Code (A.A.C.) R14-2-405.B.6 and A.A.C. R18-4-232.

REQUIREMENTS:

In compliance with the Rules of the Arizona Corporation Commission (Commission) and the Arizona Department of Environmental Quality (ADEQ), specifically A.A.C. R14-2-405-B.6 and A.A.C. R18-4-232 relating to backflow prevention:

1. The Company may require a customer to pay for and to have installed a backflow-prevention assembly if A.A.C. R18-4-232-B or C applies.
2. A backflow-prevention assembly required to be installed by the customer under Paragraph 1 of this tariff shall comply with the requirements set forth in A.A.C. R18-4-232-D and E.
3. Subject to the provisions of the A.A.C. R14-2-407 and 410, and in accordance with paragraphs 1 and 7 of this tariff, the Company may terminate service or may deny service to a customer who fails to install backflow-prevention assembly as required by this tariff.
4. The Company shall give any existing customer who is required to install a backflow-prevention assembly written notice of said requirement. If A.A.C. R14-2-410.B.1.a. is **not** applicable, the customer shall be given thirty (30) days in which to comply with this notice. If the customer can show good cause as to why he cannot install the device within thirty (30) days, the Company or Commission Staff may suspend this requirement for a reasonable period of time.

**** FOR OFFICIAL USE ONLY ****

Effective Date: March 19, 1998

APPROVED FOR FILING
DECISION #: N/A

- 5. Testing shall be in conformance with the requirements of A.A.C. R18-4-232. F. The Company may require the customer to pay to have the backflow-prevention assembly tested as long as the Company does not require an unreasonable number of tests. The Company also require the customer to pay repairs to a backflow-prevention assembly.
- 6. The customer shall provide the Company with records of installation and testing. For each backflow-prevention assembly, these records shall include:
 - a. assembly identification number and description;
 - b. location;
 - c. date (s) of test (s);
 - d. description of repairs and recommendations for repairs made by the tester; and
 - e. the tester's name and certificate number.
- 7A. In the event the backflow-prevention assembly does not function properly or fails any test, and a hazard as contemplated under A.A.C. R14-2-410.B.1.a. exists, the Company may terminate service immediately and without notice. The backflow-prevention assembly shall be repaired and replaced by the customer and retested before service is restored.
- 7B. In the event the backflow-prevention assembly does not function properly or fails any test, or in the event that a customer fails to comply with the testing requirement, and A.A.C. R14-2-410.B.1.a. is **not** applicable, the backflow-prevention assembly shall be repaired or replaced within fourteen (14) days of the initial discovery of the deficiency in the assembly or its function. Failure to remedy the deficiency or disfunction of the assembly, or failure to retest, shall be grounds for termination of water service in accordance with A.A.C. R14-2-410.

**** FOR OFFICIAL USE ONLY ****

Effective Date: March 19, 1998

APPROVED FOR FILING
 DECISION #: N/A